






701 Osage Street, Unit 120, Denver, CO 80204 USA
Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988
EMail info@bisonip.com Web www.bisonip.com




PRODUCT CHARACTERISTICS

- MAXIMUM DESIGN CAPACITY OF 1000 lbs (454 kg) FoS:3 PER PEDESTAL.
- SCREW ADJUSTABILITY WHILE PEDESTALS ARE LOADED FOR FINAL ADJUSTMENT.
- IMPERVIOUS TO FREEZE-THAW, WATER, MOLD AND SOLVENT FREE CHEMICALS.
- WEIGHT BEARING SYSTEM DOES NOT PENETRATE ROOFING MEMBRANE OR SUBSTRATE.
- LARGE FOOTPRINT SPREADS WEIGHT OVER ROOFING MEMBRANE AND SUBSTRATE.
- STANDARD PEDESTAL HEIGHTS OF 1/8" TO 24" (3 TO 610 mm).
- PEDESTAL HEIGHTS FROM 24" TO 36" (610 TO 914 mm) REQUIRE BISON BRACE SYSTEM.

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS.
2. DRAWINGS NOT TO SCALE.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com



PEDESTAL ELEVATIONS

ELEVATIONS FROM 1/8" TO 36"