




BISON Innovative Products


Get CEU Credits, Details, & Specifications online at www.bisonip.com

701 Osage Street, Unit 120, Denver, CO 80204 USA
 Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988
 EMail info@bisonip.com Web www.bisonip.com


SCREWJACK
Adjustable Pedestals




B11
 1/16" (1.6 mm) FLEXIBLE SHIM
 5-7/8" (149 mm) DIAMETER
 USED FOR SLOPE COMPENSATION,
 SOUND DAMPENING, AND/OR
 FINAL LEVELING. STACK NO MORE
 THAN 2 SHIMS.




PS1
 1/8" (3.2 mm) RIGID SHIM
 5-7/8" (149 mm) DIAMETER
 USED FOR SLOPE COMPENSATION
 AND/OR FINAL LEVELING. STACK NO
 MORE THAN 2 SHIMS.




VT316
 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
 4-11/16" (119 mm) DIAMETER
 USED FOR LOW CAVITY HEIGHTS
 AND/OR SURFACE MATERIAL SPACING.



HD25-316
 1/4" (6 mm) FIXED HEIGHT
 STACKABLE PEDESTAL
 5-7/8" (149 mm) DIAMETER
 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
 USED FOR LOW CAVITY HEIGHTS.
 STACK UP TO 4 FIXED HEIGHT
 PEDESTALS TOGETHER.




HD50-316
 1/2" (13 mm) FIXED HEIGHT
 STACKABLE PEDESTAL
 5-7/8" (149 mm) DIAMETER
 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
 USED FOR LOW CAVITY HEIGHTS.
 STACK UP TO 4 FIXED HEIGHT
 PEDESTALS TOGETHER.



HD75-316
 3/4" (19 mm) FIXED HEIGHT
 STACKABLE PEDESTAL
 5-7/8" (149 mm) DIAMETER
 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS
 USED FOR LOW CAVITY HEIGHTS.
 STACK UP TO 4 FIXED HEIGHT
 PEDESTALS TOGETHER.

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS.
2. DRAWINGS NOT TO SCALE.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com



SHIMS AND FIXED HEIGHT PEDESTALS

STACKABLE PEDESTALS FROM 1/4" TO 3"